



NEW TECH



NEW TECH

info@newtechco.de

Pycnometer



It is a machine which measures the density of a variety of solids including powder metals using the measurement of gas pressure on the basis of first rule of thermodynamic

Degree of precision

Pressure force

Sample powder capacity

Blain test



Measures specific surface area using the Fisher method designed to work automatically in accordance with ISO10070 standards



Air jet test



Equipped with a rotating grooved no=le, this machine dose the sievin through causing pressure difference in the two sides of the sieve and the particles passing through the sieve are transmitted to the vacuum machine.

The specifications of it include adaptability of no=le movement and rate of rotation.

NEW TECH



Tumbler test

Pellet corrosion resistance is one of the mechanical qualities that needs to be measured on the basis of ISO3271 and ASTM E 279



Green compression strength

GCS pellets performs the row pellet strength test.



NEW TECH

Cold Compression Strength (CCS)



It has been designed for the measurement of pellet degree of strength.

With the average capacity to testing 10 pellet per minute.

Measuring the standard deviation.

Totally automatic,

In accordance with the protocol of ISO4700 standard.

CCs on line

This machine is installed at the end of the pellet production line and tests the samples every two minutes.

The system is equipped with the screening device of 12.5.10 mm pellets and a feeder.

NEW TECH

Vibration sieve Shaker

It is used to separate and fraction the materials among the sieves in accordance to their sizes using vertical vibration.



Jaw Crusher

Jaw Crusher is the machine with a fixed and a moving jaw used for the rapid, powerful crushing and pre-crushing of medium hard, hard, brittle and tough materials such as pellet, DRI and limestone into

Vibratory Disc mill

*Grinding through pressure and friction .
Operation within 3- 1 minutes.
Movements of discs using rotory vertical vibrations .
Quick operation.
Material feed size:<5mm
Final Fineness:<150 μ m*



NEW TECH



Ball mill

*Grinding through impact friction.
Operating within 15 - 60 minutes.
Movement of balls using container
rotation.
Regular constant operation .
Material feed size: <50 mm
Final fineness:<200µm*



Mixer

*The machine for mixing iron
concentrate, bentonite and
water.
Designed in accordance with
the latest standards defined
in the material mix process.*



Vibratory feeder



*This machine prevents the
lumping of outcome concentrate
from mixing and control the
feeding loaded into the disk.*

NEW TECH



Feder conveyor

This machine receives the concentrate from the mixer constantly at an adjustable rate and carries it to the disk in the pellet production pilot plant. the flow rate of the fed into the disk is monitored constantly and online



pelletizing Disc



A disk with a diameter of 80cm is designed for the purpose of producing pellet in small quantities. Disc rotation is adjustable.



Pelletizin Pilot plant

It performs pellet production at laboratory scales. The pelletizing pilot plant is thoroughly automatic and very similar to pellet production line in the Alice Ghalimers and Lorgy methods.



NEW TECH



Pellet sieve

The baked pellet is clustered with rotating sieve.



Automatic sample Divider



Pellet sampling machine is responsible for random sampling with desirable percentage of samples. It is designed in appropriate sizes (height and width) for pellet buckets to roll in.



Riffle sample splitters

It is designed to reduce the overall sample size for the purpose of producing a sample to be used in chemical analysis laboratories. Available in three sizes with splitting sheet distances of 20, 6, and 30 mm, it is suitable for splitting a wide range of materials.



NEW TECH



Automatic Track sampler

Random sampling from a truck to test and analysis in laboratory.

The possibility of sampling with penetration in materials of varying qualities including pellet, limestone, DRI concentrate and ...

Samoler penetration to the bottom of the load.

Based on ISO3082



Automatic Sampler



Equipped with primary and secondary sampler, vibrator, excess and main sample return.

Flow of pellet is sampled totally randomly on the basis of ISO 3082


NEW TECH





Unload test

This machine measures the direct reduction degree and weight reduction of pellet under laudatory circumstances on the basis of ISO11258



Clustering test



This machine is designed for direct reduction process under load and measuring degree of clustering of DRI under laboratory circumstances on the basis of ISO 11256

Linder test

Linder test machine measures the relative fineness of pellet under the direct reduction process. It is designed based on linder and jambomidrex and in accordance with ISO 11257



NEW.TECH





Pelletizing Pilot plant



NEW.TECH



NEW TECH

www.newtechco.de